

# **SL5504**

# Pantone® Validated Signage





# Digital Signage with Pantone Validated® and Pantone® SkinTone™ Validated

Designed for those who value authentic color representation and accurate depiction of skin tones, BenQ products offer creative professionals exceptional color quality in partnership with Pantone, the world's foremost authority on color.



#### **EDLA certified Digital Signage**

You can get easy access to all core Google apps such as Chrome, Docs, and YouTube, as well as your favorite apps on the Google Play Store. You can also enjoy compatibility with Microsoft apps and tools such as Word, PowerPoint, Excel, and Teams for a versatile collaboration experience.



#### **Better device security:**

AMS and DMS, BenQ's free built-in software, provide secure login options, strict access controls, and regular system updates alongside additional protection against app vulnerabilities through





	Panel	Screen Size	55"
		Panel Surface	AG, Haze 25%
		Color gamut	sRGB 99%, 72% NTSC
		Resolution (pixels)	UHD 3840 × 2160
		Active area (H × V)	1209.6 × 680.4
		Brightness (typical)	500 nits
		Contrast Ratio (typical)	1200:1
		Light Life (typical)	50,000hrs
		Display Orientation	Landscape / Portrait
	Platform Solution	Memory   Storage   OS	8GB   64GB   Android 13.0
	Speaker	Internal Speaker	12 W × 2
S	Connectivity Physical	HDMI (in   out)	×2 (2.0 × 2)   No
		Line in / out (3.5mm)	N/A   ×1
		Ethernet LAN	1 × 10 / 100 Mbps (Android)
		USB (Type A)   (Type B)	×2 (2.0 × 2)   No
		RS232 ( in   out)	×1   ×1
		Power (AC) In   Out   Power	11N/A11
		Switch	14.7 kg   19.1 kg (32.4 lbs   42.1
		Weight (product I shipping)	lbs)
		Dimensions (W x H x D)	1237.3 × 709.8 × 56.4 mm (48.7 × 27.9 × 2.2 inch)
		Danel wielth (TIDIIID)	12   12.8   12   12 mm (0.5   0.5
		Bezel width (TIBILIR)	0.5   0.5 inch)
		Wall Mounting (VESA)	4 - M6 × 12L
	Power	Voltage	100V ~ 240V, 50Hz / 60Hz
		Typical	81.9 W
	Environment	Operation Temperature	0°C ~ 40°C   32°F ~ 104°F
		Storage Temperature	-10°C ~ 60°C   14°F ~ 140°F
	Language	OSD	28L (AR, CS, DA, DE, EL, EN, ES- ES, FA, FI, FR, HE, HU, ID, IT, JA,
			KO, NB, NL, PL, PT-BR, RO, RU, SV,
			TH, TR, VI, ZH-CN, ZH-TW)
	Package	Remote Controller	Yes
		Power Cord	By region
		Cables	1 × HDMI (1.5 m   4.9 ft)
	Software	Content management	X-Sign 3.0
		Device Management	DMS
		Account Management	AMS
		Wireless screen sharing	InstaShare 2
	Picture mode	Pantone, M-book, Coding, ePo	aper
	'		

#### Software









# X-Sign

Wireless screen sharing & casting from any device. Share several screens simultaneously, with different types of content.

## InstaShare 2

Wireless screen sharing & casting from any device. Share several screens simultaneously, with different types of content.

## **DMS**

Device Management Solution centrally oversees all displays to get real-time status information, deploy OTA updates & more.

#### **AMS**

Account Management System to conveniently load and access your account and cloud storage from any BenQ display.

## Input and output terminals

#### Down I/O















USB 2.0

USB 2.0

LAN


Audio out


in

HDMI

HDMI

## Dimensions (mm)





# **Benq**

© 2024 BenQ Corp. Specifications may vary by region, please visit your local stores for details. The actual product's features and specifications are subject to change without notice. This material may include corporate names, trademarks and logos of third parties which are the properties of the third parties respectively.



https://education.benq.com/