



Windows 11 Pro Fully Rugged Laptop with 14.0"
Outdoor Display and Modular Expansion Areas...

## **TOUGHBOOK 40**

The 14.0" fully-rugged Panasonic TOUGHBOOK 40 laptop breaks new ground offering unrivaled flexibility in even the most demanding and unpredictable environments, including Defence, Mining and Utilities. It has a modular design that allows mobile workers to modify the device quickly and easily for different challenges by equipping 8 expansion areas. The powerful rugged laptop is built for use in the most extreme conditions and designed for field specialists, incorporating quick release self-encrypting secure drives and providing up to 36-hours of battery life to support mission critical operations.

## **Key Features**

Intel® Core™ i5-1145G7 vPro™ Processor (optional Intel® Core™ i7-1185G7 vPro™\*)

## Windows 11 Pro

14.0" Active Matrix (TFT) colour LCD 1920  $\times$  1080 (FHD) with sunlight-viewable glove-enabled touchscreen (up to 1,200cd/ $m^2$ )

Up to 180cm drop resistance\*\*\*, IP66 water and dust resistance, MIL-STD 810H certified\*\*\*

Long battery life of up to 18 hours (up to 36 hours with optional 2nd battery\*)











## TOUGHBOOK 40

https://oc.connect.panasonic.com/au/en/products/toughbook/toughbook-40

Mobile Computing Platform	Intel® Core™ i5-1145G7 vPro™ Processor (optional Intel® Core™ i7-1185G7 vPro™*)
Operating System	Windows 11 Pro
RAM	Built-in 16GB RAM (max 64GB RAM*)
Graphic Chip	Intel® UHD Graphics, supports Intel® Iris® Xe Graphics when 2 RAM Modules installed
Storage	Quick release 512GB NVMe OPAL SSD (with heater)
LCD	14.0" Active Matrix (TFT) colour LCD 1920 x 1080 (FHD) LCD with sunlight-viewable glove-
	enabled touchscreen (up to 1,200cd/m² brightness)
Bluetooth™	5.1 Class 1
Wireless LAN	Intel® Wi-Fi6 AX201
Mobile Broadband*	4G LTE
GPS*	U-Blox NEO-M8
LAN	IEEE 802.3 10Base-T / IEEE 802.3u 100BASE-TX / IEEE 802.3ab 1000BASE-T (optional 2nd
	GLAN*)
Sound	Waves MaxxAudio® Stereo Speakers
	·
	4 integrated microphones
Security	TPM 2.0, Password security, Integrated hardware security lock slot
Front Camera	5MP with IR / privacy shutter (Windows Hello compliant) optional*
USB 3.2	x2 (Gen 1 Type-A)
Thunderbolt 4	x1
Micro SDXC Memory Card	x1
HDMI	x1
Headset	x1
DC In	x1
Port Replicator	x1
Quad Path Through Connector Left Expansion Area**	x1 2nd SSD
	Smart Card Reader  DVD Multi Drive  Blu Ray Drive
Right Expansion Area**	2nd Battery
	Smart Card Reader
Rear Expansion Area**	VGA + True Serial (RS232) + 2nd native GLAN
	USB 3.1 Type A + True Serial (RS232) + 2nd HDMI
	USB 3.1 Type A + USB 3.1 Type A + 2nd HDMI
Palm Rest Expansion Area**	Fingerprint reader (Windows Hello)
	Fingerprint reader (Windows Hello, Multi-user authentication)
	Contactless Smart Card Reader
AC Adapter	Input: 100V - 240V AC, 50Hz/ 60Hz, Output: 15.6V DC, 7.05A
Battery	Lithium-Ion 10.8V, 6500mAh (typical), 6300mAh (minimum)
Battery Life	Standard: approx 18 hours (Mobile Mark™ 2014)
N	With optional 2nd battery: approx 36 hours (Mobile Mark™ 2014)*
Power Management	Standby function, ACPI BIOS
Dimensions (WxHxD)	354mm x 301mm x 54.4mm (without protruding parts)
Weight	Approx 3.35kg (depending on configuration)
-	MIL-STD810H, 180cm***
Drop Resistance	
Drop Resistance Dust Resistance	IP6x
Drop Resistance Dust Resistance	IP6x IPx6
Drop Resistance Dust Resistance Water Resistance	
Drop Resistance Dust Resistance Water Resistance Operating Temperature	IPx6
Dust Resistance Dust Resistance Water Resistance Operating Temperature Standard Configuration Included in the box	IPx6 MIL-STD810H, -29°C to +63°C***

<sup>\*\*</sup>One option exclusive possible in configuration port / business expansion module

<sup>\*\*\*\*</sup>Tested by an independent third party lab following MIL-STD810H Method 516.8 Procedure IV for transit drop test and Method 501.7 and 502.7 Procedure II for operation temperature test. May differ depending on models and options