



HP 65W USB-C LC Power Adapter (1P3K6AA)



Overview

Powerful USB-C® charging

Charge your laptop in the office or on the go with the HP USB-C LC Power Adapter.

Connect easily

The HP USB-C LC Power Adapter works with any of your laptops' USB-C® ports[1] so you can stop worrying about finding the right adapter.

World-class support

Rest easy with a one-year limited warranty.

Quick charging

Charge your laptop quickly with the HP USB-C LC Power Adapter's HP Fast Charge Technology[2].

[1] Adapter supports up to 65W power delivery. See HP product Quick Specs for compatibility.

[2] HP Fast Charge charges 50% in 30 minutes or 90% in 90 minutes, depending on HP platform with 65W AC Adapter defined under system hibernation and off mode. After charging has reached 50% or 90% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

Specifications

Dimensions (W x D x H)	9 x 5.1 x 2.85 cm
Dimensions (W x D x H)	3.54 x2 x 1.12 in
Weight	0.235 kg
Weight	0.51 lb
Minimum System Requirements	USB Type-C® port
UPC number	195122442989
Manufacturer Warranty	1 Year Limited Warranty (Return to HP/Dealer - Standard Bench Repair & Phone-in Assistance)
What's in the box	AC power adapter; USB Type-C® cable; 1 Power Cord; Warranty Card

Additional specifications

Cable length	180 cm (power cord); 180 cm (USB Type-C® cable)
Cable length (imperial)	70.9 in (power cord); 70.9 in (USB Type-C® cable)
Certifications and compliances	CE Mark; IEC 60950-1; EN 60950-1; UL 60950-1; UL 62368-1; SELV; C-UL-US; DENAN; EN 55022 Class B; FCC Class B; CCC; NOM-1 NYCE; NORDICS; CISPR 22 Class B; MTBF
Compatibility	Compatible with HP Chromebox G3; HP Chromebox G4; HP Dragonfly Folio 13.5 inch G3 2-in-1 Notebook PC; HP Elite c640 14 inch G3 Chromebook; HP Elite c645 14 inch G2 Chromebook; HP Elite Dragonfly 13.5 inch Chromebook; HP Elite Dragonfly 13.5 inch G3 Notebook PC; HP Elite x360 1040 14 inch G9 2-in-1 Notebook PC; HP Elite x360 830 13 inch G9 2-in-1 Notebook PC; HP EliteBook 1040 14 inch G9 Notebook PC; HP EliteBook 830 13 inch G9 Notebook PC; HP EliteBook 835 G7 Notebook PC; HP EliteBook 840 14 inch G9 Notebook PC; HP EliteBook 845 G7 Notebook PC; HP EliteBook 855 G7 Notebook PC; HP EliteBook 860 16 inch G9 Notebook PC; HP EliteBook x360 1030 G7 Notebook PC; HP EliteBook x360 1040 G7 Notebook PC; HP EliteBook x360 830 G7 Notebook PC; HP Fortis 11 inch G9 Q Chromebook; HP Pro c640 G2 Chromebook; HP Pro x360 Fortis 11 inch G11 Notebook PC; HP ProBook 440 14 inch G10 Notebook PC; HP ProBook 440 14 inch G9 Notebook PC; HP ProBook 445 14 inch G9 Notebook PC; HP ProBook 445 G7 Notebook PC; HP ProBook 450 15.6 inch G10 Notebook PC; HP ProBook 455 G7 Notebook PC; HP ProBook 635 Aero G7 Notebook PC; HP ProBook Fortis 14 inch G10 Notebook PC; HP ProBook Fortis 14 inch G11 Notebook PC; HP ProBook Fortis 14 inch G9 Notebook PC;
Connection type	USB Type-C®
Datasheet photo 1	AHID/f1cef6c06a379d6d636efd39363455718fe191b5
Hold-up time	5 ms at 115 VAC input
Input efficiency	89% min at 115 VAC/230 VAC at 20V/3.25A
Input frequency	47-63 Hz
Input operating current	1.6 A at 90 VAC max
Non-Operating Humidity Range	10 to 95% RH
Operating altitude	Up to 5,000 m
Operating altitude	Up to 16,400 ft
Operating humidity range	20 to 95% RH (non-condensing)
Operating temperature range	0 to 35°C
Operating temperature range	32 to 95°F
Output current limit	8 A max
	65 W
Output power	65 W
Over-voltage protection	20V: 29V
Product long name specifications	HP AC Adapter

Product subgroup	Adapter
Storage temperature range	-4 to 185°F
Storage temperature range	-20 to 85°C
UNSPSC code	39121006

Disclaimer — Copyright

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (au-en) – Aug 20, 2025 5:23 AM UTC+0000