

CASES

iM2950

Pelican Storm Case



iM2950 Pelican Storm Case

- Five Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

iM2950 Pelican Storm Case Configurations

Cat. #	Description
iM2950-X0001	iM2950 Pelican Storm Case
iM2950-X0000	iM2950 Storm Case (No foam)
iM2950-X0002	iM2950 Storm Case with Padded Dividers



Black



Yellow



OD Green

iM2950 Pelican Storm Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
31.30" x 20.40" x 12.20" (79.5 x 51.8 x 31 cm)		29.00" x 18.00" x 10.50" (73.6 x 45.7 x 26.7 cm)	
Lid Depth		Bottom Depth	Total Depth
2.00" (5.1 cm)		8.50" (21.6 cm)	10.50" (26.7 cm)
Interior Cubic Volume			
3.17 cubic feet (89.82 cubic decimeter)			
Weight with foam	Weight without foam	Buoyancy Max.	
28.7 lbs. (13.02 kg)	20.8 lbs. (9.43 kg)	260.65 lbs. (118.23 kg)	
Range Temperature	No. of Wheels	Retractable Handle	
-20 / 140° F (-29 / 60° C)	2	YES	

iM2950 Pelican Storm Case Certificates

iM2950 Pelican Storm Case Accessories

Cat. #	Description
iM-LIDSTAY	Lid Stay
iM-VALVE-M-B	Manual Purge Valve
iM2950-DIV	Padded Dividers
iM2950-FOAM	6 pc. Replacement Foam Set
iM29XX-BEZEL	Base Bezel Kit
iM29XX-BEZEL-LID	Lid Bezel Kit
iM29XX-UTILITYORG	Utility Organizer

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com